

## WLI ROOF ESCAPE WINDOW



### Features

-  Designed for uninhabited lofts with the interior temperature similar to the outdoor temperature.
-  Frame manufactured from vacuum impregnated pine wood.
-  It comes complete with a turn limiter to hold the sash table and prevent accidental closure.
-  Equipped with a universal flashing to match every roofing material.
-  Special handle enables locking the sash in three positions hence allowing space ventilation.
-  Easy installation on trimmers, enables moving the roof access window during installation in horizontal position in order to better adjust it to the roofing material.
-  Sash made of aluminium profile with chamber structure along with 1.6mm thick glazing unit ensure proper rigidity.
-  Installation in roof pitches from 15 to 60 degrees.
-  Toughened pane with increased resistance to hail and mechanical impact.

## WGT TOP HUNG ESCAPE WINDOW



### Features

-  Frame is made of pine wood, vacuum impregnated.
-  Sash is made of aluminium, powder painted grey, fitted inside with a peripheral seal.
-  Has a handle that allows the sash to be secured in two positions to ventilate the room.
-  Suitable for roofs with pitches between 15 and 55 degrees.
-  Window integrated with universal flashing with lead apron.
-  Toughened glass with increased resistance to hailstones.
-  Specially rounded locking bolts exclude possibilities of injuries.
-  Easy fitting system on battens does not require additional trimmings.
-  Fitting kit included with the window.

### Window external

WLI with universal flashing	54 x 83
WGTwth universal flashing	46 x 55